



Winkelstahl

scharfkantig, gleichschenkelig

Abmessung	kg/mtr.
10/10/2	0,28
15/15/ 2	0,44
15/15/ 3	0,64
20/20/ 2	0,60
20/20/ 3	0,87
25/25/ 2	0,75
25/25/ 3	1,11
25/25/ 4	1,44

Abmessung	kg/mtr.
30/30/ 2	0,91
30/30/ 3	1,34
30/30/ 4	1,76
35/35/ 3	1,58
35/35/ 4	2,07
40/40/ 3	1,81
40/40/ 4	2,39
40/40/ 5	2,94
45/45/ 5	3,34

Abmessung	kg/mtr.
50/50/ 4	3,01
50/50/ 5	3,73
60/60/ 5	4,55

Winkelstahl

scharfkantig, ungleichschenkelig

Abmessung	kg/mtr.
20/10/ 3	0,64
20/14/ 3	0,73
25/15/ 3	0,87
30/20/ 3	1,11
30/20/ 4	1,44

Abmessung	kg/mtr.
40/20/ 3	1,34
40/20/ 4	1,76
40/25/ 3	1,46
40/25/ 4	1,92
45/30 4	2,23
50/25/ 3	1,70
50/25/ 4	2,25

Abmessung	kg/mtr.
50/40/ 4	2,70
60/30/ 3	2,05
60/40/ 4	3,01



T- Stahl

breitfüßig, rundkantig

Abmessung	kg/mtr.
40/20/4,5	2,01
50/25/5,5	2,80
60/30/5,5	3,64

Abmessung	kg/mtr.
70/35/6,0	4,66
80/40/7,0	6,21
100/50/8,5	9,42

Abmessung	kg/mtr.
120/60/10	13,40

T- Stahl

breitfüßig, scharfkantig

Abmessung	kg/mtr.
30/20/ 3,0	1,11

Abmessung	kg/mtr.
40/20/ 3,0	1,34

T- Stahl

mit versetzten Steg

Abmessung	kg/mtr.
40/30/ 3/12	1,58

Abmessung	kg/mtr.
50/35/ 4/12	2,54

Z- Stahl

scharfkantig

Abmessung	kg/mtr.
16/25/25/3,5	1,62
25/16/16/3,5	1,35
30/35/17/4,0	2,32
35/30/18/3,0	1,82
40/22/17/4,5	2,47

Abmessung	kg/mtr.
40/35/25/4,0	2,90
48/50/25/4,0	3,65
50/30/25/5,5	4,06
54/50/25/4,0	3,81



Z- Stahl

rundkantig

Abmessung	kg/mtr.
30/38/38/4/4,5	3,36
40/40/40/4,5/5	4,26
50/43/43/5/5,5	5,31

Abmessung	kg/mtr.
60/45/45/5/6,0	4,26
80/50/50/6/7,0	8,71

Rolladen-U- Stahl

scharfkantig

Abmessung	kg/mtr.
15/20/ 1,5	0,66
20/20/ 2,0	0,88
25/25/ 2,0	1,11
30/30/ 2,0	1,35
33/33/ 3,0	2,19
36/36/ 3,0	2,35

Abmessung	kg/mtr.
40/20/ 3,0	1,78
40/40/ 3,0	2,68
50/30/ 3,2	2,65
50/30/ 4,0	3,20
50/50/ 4,0	4,46
60/30/ 3,0	2,68

U- Baustahl

(Fahrzeugbau- U)

Abmessung	kg/mtr.
40/35/ 4,0	3,02
40/40/ 3,0	2,47
46/45/ 3,0	2,92
50/40/ 4,0	3,67
54/45/ 4,0	4,12
62/45/ 4,0	4,53
70/50/ 4,0	5,13

Abmessung	kg/mtr.
80/50/ 5,0	6,40
90/50/ 5,0	6,80
100/50/ 5,0	7,22
120/60/ 6,0	10,39
140/60/ 6,0	11,10
160/65/ 6,0	12,75



Bordwand-U

rundkantig

Abmessung	kg/mtr.
20/20/ 1,5	0,67
23/23/ 1,5	0,77
25/25/ 1,5	0,83

Abmessung	kg/mtr.
28/28/ 1,5	0,94
30/30/ 1,5 30/30/ 2,0	1,01 1,34
36/36/ 3,0	2,35

Bodenbelag-Winkel

Abmessung	kg/mtr.
40/40/ 5	3,30
50/50/ 5	4,51

Abmessung	kg/mtr.
50/50/ 7	5,60
50/50/10	5,80

Handleistenstahl

Abmessung	kg/mtr.
40/18/ 8	3,35

Abmessung	kg/mtr.
50/22/5/10	5,30

Halbrundstahl

Abmessung	kg/mtr.
30/15	2,77

Abmessung	kg/mtr.
40/20	4,92



Hespenstahl

Abmessung	kg/mtr.
30 x 8	1,26
40 x 12	2,25

Treppenschutzschienen- Profil

Abmessung	kg/mtr.
35 mm	1,75