



Feinbleche St 12.03, blank

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
0,50 mm	8	---	---
0,63 mm	10	---	---
0,75 mm	12	19	27
0,88 mm	14	22	32
1,00 mm	16	25	36
1,25 mm	20	31,5	45
1,50 mm	24	37,5	54
2,00 mm	32	50	72
2,50 mm	40	62,5	90
2,99 mm	48	75	108

Feinbleche, elektolytisch verzinkt

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
0,63 mm	---	---	---
0,75 mm	12	19	27
0,88 mm	14	22	32
1,00 mm	16	25	36
1,25 mm	20	31,5	45
1,50 mm	24	37,5	54
2,00 mm	32	50	72
2,50 mm	40	62,5	90
2,99 mm	48	75	108




Feinbleche, sendzimirverzinkt (feuerverzinkt)

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
0,50 mm	8	---	---
0,63 mm	10	---	---
0,75 mm	12	19	27
0,88 mm	14	22	32
1,00 mm	16	25	36
1,25 mm	20	31,5	45
1,50 mm	24	37,5	54
2,00 mm	32	50	72
2,50 mm	40	62,5	90
2,99 mm	48	75	108
4,00 mm	64	100	144
5,00 mm	80	125	180

Wellbleche, sendzimirverzinkt (feuerverzinkt)

Format	920 x 2000 mm	920 x 2500 mm	920 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
0,63 mm	10	12	14
0,75 mm	12	14	17

Auf Bestellung sind alle Wunschlängen innerhalb von 2-3 Wochen zu erhalten.
 Die Baubreite bleibt dabei immer 920 mm.



Grobbleche S235JRG2

verzundert

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
1,5 mm	24	---	---
2 mm	32	50	---
3 mm	48	75	108
4 mm	64	100	144
5 mm	80	125	180
6 mm	96	150	216
8 mm	128	200	288
10 mm	160	250	360
12 mm	192	300	432
15 mm	240	375	540
20 mm	320	500	720
25 mm	400	625	900
30 mm	480	750	1080
35 mm	560	875	1260
40 mm	640	1000	1440
50 mm	800	1250	1800
60 mm	960	1500	2160



Grobbleche STW 22 gebeizt

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
4 mm	64	100	144
5 mm	80	125	180
6 mm	96	150	216
8 mm	128	200	288
10 mm	160	250	360



Tränenbleche S235JRG2

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
3 mm	58	79	---
4 mm	68	107	153
5 mm	84	132	189
6 mm	102	160	230
8 mm	134	209	302
10 mm	166	260	374
12 mm	198	310	446

Tränenhöhe ca. 2 mm (je nach Grunddicke)

Riffelbleche S235JRG2

Format	1000 x 2000 mm	1250 x 2500 mm	1500 x 3000 mm
Stärke	<i>kg/Tafel</i>	<i>kg/Tafel</i>	<i>kg/Tafel</i>
3 mm	58	91	---
4 mm	76	119	171
5 mm	92	144	207
6 mm	108	169	243
8 mm	140	219	315
10 mm	172	269	387
12 mm	204	319	459

Riffelhöhe ca. 2 mm (je nach Grunddicke)